



EnergyCell RE Front Terminal

VRLA Battery for Renewable Energy Storage



- Front Terminal Access Design for Ease of Maintenance and Installation
- High-Density Pasted Plates for High Cycle Life
- Lead-Calcium-Tin Alloy Plates for Long Life in Both Cycling and Float Applications
- High Recharge Efficiency
- Compact Footprint for Higher Energy Density Requirements
- Thermally Welded Case-to-Cover Bond to Eliminate Leakage
- UL-Recognized Component
- Up to 2-Year Full Replacement Warranty

The EnergyCell RE Valve Regulated Lead Acid (VRLA) battery is designed for high power density and renewable energy cycling applications.

Absorbed Glass Matt (AGM) technology provides for efficient gas recombination of up to 99% and freedom from electrolyte maintenance. The EnergyCell RE also features low profile terminals with threaded copper alloy inserts providing reduced maintenance and increased safety.

EnergyCell RE Models:	EnergyCell 170RE	EnergyCell 200RE
Cells per Unit	6	6
Voltage per Unit	12VDC	12VDC
Operating Temperature Range (w/ temperature compensation)	Discharge: -40 to 71°C (-40 to 160°F) Charge: -23 to 60°C (-10 to 140°F)	Discharge: -40 to 71°C (-40 to 160°F) Charge: -23 to 60°C (-10 to 140°F)
Optimal Operating Temperature Range	23 to 27°C (74 to 80°F)	23 to 27°C (74 to 80°F)
Float Charging Voltage	13.62VDC / unit average at 25°C (77°F)	13.62VDC / unit average at 25°C (77°F)
Absorbed Voltage	14.4VDC / unit average at 25°C (77°F)	14.4VDC / unit average at 25°C (77°F)
Maximum Charge Current	46.14A	53.40A
Self Discharge	Battery can be stored up to 6 months at 25°C (77°F) before a freshening charge is required. Batteries stored at temperatures greater than 25°C (77°F) will require recharge sooner than batteries stored at lower temperatures.	
Temperature Compensation Factor (Charging)	5mV per °C per cell (2V)	5mV per °C per cell (2V)
Terminal	Threaded copper alloy insert terminal to accept ¼"-20 UNC bolt	Threaded copper alloy insert terminal to accept ¼"-20 UNC bolt
Terminal Hardware Initial Torque	110in-lbs (12.4Nm)	110in-lbs (12.4Nm)
Weight	115 / 52	131 / 60
Dimensions H x D x W (in/cm)*	11.14 x 22.01 x 4.95 / 28.3 x 55.9 x 12.6	12.60 x 22.01 x 4.95 / 32.0 x 55.9 x 12.6

Discharge in Hours:	12V Ampere Hour Capacity to 1.75 Volts Per Cell at 77°F (25°C)										
	1	2	3	4	5	8	12	20	24	48	100
EnergyCell 170RE	89.1	103.5	114.3	120.4	126.0	136.8	145.2	153.8	156.9	163.6	169.9
EnergyCell 200RE	103.0	120.0	132.0	139.6	145.5	158.4	168.0	178.0	181.4	189.6	200.0

*Batteries to be installed with 0.5 in (12.7 mm) spacing minimum and free air ventilation.

Worldwide Corporate Offices

